Note to our customers:

Please use this form to supply your specification data and submit the completed form to your Tranter Sales Representative.



SPECIFICATION SHEET

Customer			Date				
Attention			Plant Location				
Street			City/State	Zip			
Item No.			Phone No				
Fax No.			Project No.				
Project Reference Description							
Application	Mo						
Number of Units	No. Plates/Unit	Connected i□ Series □			Paralle	:l	
Total Surface	Sq.Ft. Su			rface Per Unit Sq.Ft.			
PERFORMANCE	HOT SIDE			COLD SIDE			
Fluid Circulated							
Total Flow Rate							
Specific Heat	Btu/(lb)°F					Btu/(lb)°F
Specific Gravity							
Thermal Conductivity	Btu/(hr)(ft)°F					Btu/(hr)(
Viscosity (at 2 temps)	cp@ °F	cp@	°F	cp@	°F	cp@	°F
Temperature In			°F				°F
Temperature Out			°F				°F
Pressure Drop			psi				psi
Operating Pressure			psig				psig
Heat Exchanged						В	tu/hr
CONSTRUCTION							
Design Pressure							
Test Pressure		ASME □	ABS	□ DNV		Othe	r
Design Temperature	Type of Connection: □ F	Flanged 🗆	Studd	ed Port □	Pipe		
MATERIAL							
Gaskets:							
Nozzles:							
Frame:							
Plates:							
REMARKS:							

SUPERCHANGER performance is conditioned on the accuracy of the data presented and the customer's ability to supply equipment and product conformance with the above.