Tri-Clover®

Pump Specification Data Sheet

General Information				
Company Name:				
Address:				
City:	State: Zip:			
Material Pumped:				
Weight:	lbs. per gal.	Viscosity:	cent	ipoise
Specific Gravity:		Temperature (Min.): _	°F	
Corrosive (Yes/No):	Temperature (N		°F	
Abrasive Content:				
Material Similar To:	Size of Particles: (ave			rage)
Capacity Required:	gal. per min. Capacity Required:		lbs.	per hr.
This pump will be used for:	□ new application □ replacement pump)
2 Suction Line Is the line flooded: Yes No Vertical Drop to Pump:	foot	Casing Drain: Yes		
Pipe Size: Connection Type: Bevel Seat Tri-Clamp® Horizontal Pipe:	inches	Indicate Port Size:	□ Flanged □ Other:	
3 Discharge Line				
Pipe Size:	inches	Sterile B	arrier Req'd: Yes	No
Connection Type:	feet	□ N.P.T □ Weld Horizontal Pipe:		
Number of Elbows:	feet	Discharge through of	ther equipment: Yes	5 No
Discharge Valve: Yes No		Discharge Pressure:		lbs.



Pump Motor

Service Cycle:	hrs. per	day			
Type of Drive:	Variable Speed	□ V-Belt	🗆 Gearhead	Other:	
Motor Specs:	□ AC □ DC	Volt:	Cycle:	Phase:	
Type of Drive:	Easy Clean	□ Explosio	n Proof	□ Totally Enclosed	🛛 Open
5 Replacement Pu	ımp				
Current Manuf	facturer:		M	odel:	
Se	eal Type:		Horsepo	ower:	
	RPM:				
Reason for	Change:				

6 Sketch of Installation





To: Centro, Inc.	From:
Fax:	Pages:
Phone: 800-344-3286	Date:
Re:	CC:

Please fill out the following specification form and fax to one of our five locations:

Memphis: 901-357-1379 Little Rock: 501-835-2277 Nashville: 615-255-2212 El Dorado, AR: 870-881-8400 Shreveport: 318-390-9878

